



Technical Documentation

ICE-CREAM FREEZERS

BYFAL sp. z o.o.

ul. Perłowa 17
77-132 Niezabyszewo



More information at: www.byfal.pl

Information card


Ice-cream freezer with a direct sales function is intended for display and sale of frozen products.


Model identifier		ZL-601
Device range code		HF7
Net volume	[dm³]	458
Target temperature	[°C]	-14
Duration of the guarante	24	
Minimum ambient temperature / humidity	[°C/%]	16 / 80
Maximum ambient temperature / humidity	[°C/%]	35 / 75
Annual energy consump	tion [kWh/a]	803
EEI		35
Energy efficiency class	С	
Additional lighting	Lack	
Holes for containers		11




Dimensions

L	Lw	S	Sw	Н	Hw	Packing LxSxH	Net weight	Gross weight
1600	1440	755	543	890	630	1,65 x 0,80 x 0,93	76	90







Specification

The freezer is built in the shape of a horizontal cabinet. Freezer walls are insulated with polyurethane foam. Outer coat is made of galvanized sheet metal covered with PVC which makes it resistant to corrosion and scratches. Side interior walls of the freezer are made of 99% pure aluminum sheet and the bottom is made of steel sheet covered with a coating that is approved for contact with food. An evaporator is placed under the aluminum sheet. On the front wall under the outer coat there is a condenser. Cover is made with holes for containers. In addition, the refrigeration system includes a compressor and expansion valve in the form of a capillary tube and a filter. An electronic controller is used to control the compressor operation. This allows you to change the setting of the desired cooling temperature and additionally displays the current temperature of the cooling chamber.

Value Power supply V/ 240 / 50 Hz Current A 0,6/8,2nom./max. Installed W 143 power Wheels $2+2_{\text{hamulcem}}$ refrigerant IP R290 Refrigerant 70 g dose Defrosting manual

General product specifications (UE)2019/2018 zał. VI pkt 1.b.

Parameter	Value	Parameter	Value
Annual energy consumption (kWh/a)	803	Standard annual energy consumption (kWh/a)	2294,71
Daily energy consumption (kWh/24h)	2,2	Ambient conditions	Set 2
M	2,0	N	0,009
Temperature coefficient (C)	1,00	Y	476,32
P	1,00		
Climate class factor (CC)	1,04	Target temperature (Tc) (°C)	-18,0

Additional information

The product complies with the following harmonised standards:

PN-EN PN-EN 60335-1:2012/A14:2020-05

PN-EN 60335-2-24:2010

PN-EN 55014-1:2017-16

PN-EN IEC 61000-3-2:2019-04 PN-EN 61000-3-3:2013-10

PN-EN 61000-4-2:2011

PN-EN 61000-4-4:2013-05

PN-EN 61000-4-5:2014-10

PN-EN 61000-4-6:2014-04

PN-EN IEC 61000-4-11:2020-11

Model identifier

Ice-cream freezer **ZL-601**/X

/X – the number of holes in the lid

So when ordering **ZL-601/11** model we get: ice-cream freezer ZL-601 with 11 holes for containers in the lid as in the example photo on page 1 of this information sheet.

Special precautions

- Pleas read manual carefully before unpacking and installing. To ensure safety, the instructions must be strictly followed.
- The appliance may be connected to the mains by an authorized person after reading the manual. The connection can by done only to a grounded socked to avoid electric shock.
- It is forbidden to make holes in the housing of the device. It may cause release of flammable refrigerant.
- Air vents in the housing of the appliance must not be obstructed.
- The freezer should be placed in such a way that the plug is accessible.
- You can not obstruct the front wall of the freezer or stick on it thick insulating stickers.
- Make sure that the appliance is not standing on the power supply cable.
- Install the appliance in a dry room with the area of not less than 4m², above the ground level. Avoid locations near a source of heat or in direct sunlight. The temperature in the room must not be lower than 16°C.
- Do not leave the device on a slope without the braked wheels.
- Installation and maintenance of the appliance may not be done by persons (including children) with reduced physical, sensory or mental capabilities.
- Do not store glass containers with liquids, electrical appliances or other objects with sharp edges inside the freezer.
- In the case of freezer failure or damage the power cable insulation, repairs may by made only by a person authorized to repair this type of appliance.
- Attention! Danger of explosion or fire.

The installation contains flammable gas. Perforation of the internal or external walls of the housing can cause escape of the flammable refrigerant.

If such a case occurs, the lid should not be closed. Do not use near open flames or sparking devices. Disconnect the appliance from the mains power supply, remove it outside and only there you can take out the products.

Energy efficiency class:

Determination of the energy efficiency class in accordance with the Commission Delegated Regulation (EU) 2019/2018 of 11 March 2019r.

Ad.1 Ambient conditions.

Dry bulb temperature	Relative humidity	Dew point	Water vapour mass in dry air, [g/kg]
30	55	20,0	14,8

Ad.2 Determination of the EEI:

$$AE = 365 \text{ x } E_{daily} = 365 \text{ x } 2,2 = 803$$

$$Y = V_{netto} x ((12-Tc)/30) x CC = 458 x 1 x 1,04 = 476,32$$

SAE =
$$365 \times P \times (M + N \times Y) \times C = 365 \times 1 \times (2,0 + 0,009 \times 476,32) \times 1 = 2294,71$$

$$\mathbf{EEI} = AE/SAE = 805,92 / 2376,70 = 0,35 \times 100 = 35\%$$

 $E_{\mbox{\tiny daily}}$ - Determined in a laboratory test in accordance with ISO 23953-2:2016-04

Energy efficiency	Energy efficiency	
classes	index	
A	EEI< 10	
В	10 <=EEI< 20	
С	20 <=EEI< 35	
D	35 <=EEI< 50	
E	50 <=EEI< 65	
F	65 <=EEI< 80	
G	EEI>= 80	

